



CALIDUS™ 301 micro Gas Chromatograph

GC analysis for virtually any fixed gas and hydrocarbons up to C₄₄ for laboratory, at-line, transportable or online use

- **Upstream (E&P)**
- **Petrochemical/Chemical**
- **Food & Beverage**
- **Military**
- **Refining**
- **Pharmaceutical**
- **Medical**
- **Educational**



CALIDUS Model 301 - comprised of 5 modules

A single Sample Processing Unit with a standard split/splitless injection port (1:1 up to 1:200) suitable gas and liquid samples via either syringe through the septum injections, optional gas, liquid or headspace auto-sampler, or automated sampling valves. The inlet includes septum purge to prevent bleed components from entering the system. The sample is then delivered to a sample splitter for analysis on two independent column modules.

Two Programmed Temperature Column Modules (PTCM) in parallel containing the resistively heated steel capillary chromatography column with necessary hardware, software and electronic control to enable temperature programming from 0.1°C to 5°C per second from 5°C above ambient to 350°C depending on the maximum temperature capability of the column material selected. Each column module is independently controlled by the method and can be any of the available column types.

Two independent Detector Modules incorporating either a micro Flame Ionization Detector (FID) or micro Thermal Conductivity Detector (TCD) with the necessary hardware, software and electronic control to provide detector temperature control, digital output signal and additionally for proper FID fuel supply pressure and auto-ignition.

The micro FID is a fully digital carbon/hydrogen bond detector using the hydrogen flame to burn the sample components. It uses an electrometer to sense the current changes in the flame cell due to chromatographic component elution. The data rate is 100 Hz.

The micro TCD is a fully digital, universal detector. The TCD consists of a constant temperature filament that senses change in power required to hold the filament temperature constant when chromatographic components elute. The power measurement is used to determine the amount of the component eluting from the column. The data rate is 50 Hz.

CALIDUS is controlled with ChromPerfect chromatography data system fully integrated with LineUp running on a Windows PC.



100 AEI Drive
Fairlea, WV 24901
P.O. Box 518

Phone: 304-647-5860
Fax: 304-645-4006
E-mail: info@falconfast.net

SIGNIFICANCE AND USE

The Model 301 provides a simple ultra-fast analysis (10 to 50 times faster than conventional lab or process GC's) of fixed gases and hydrocarbons to C₄₄. Use of two different PTCMs in parallel with their own detectors for example one TCD and one FID with the appropriate column material enables leveraging the sensitivity and selectivity differences for enhanced separations. Proper choice of columns enables wide boiling range and concentration ranges with a single GC.

The analyses are used for product specifications testing, product safety, environmental measurements, process control, catalyst protection, educational tools, spot checks of fuels and many more.

Faster, Smaller, Smarter, Easier, Greener



UK Distribution by: IMA Ltd, Parkwell House, Otley Road, Guiseley, West Yorkshire, LS20 8BH, England
Tel: +44(0)1943 878877 Email: info@ima.co.uk Website: www.ima.co.uk



CALIDUS™ 301 Specifications (global patents pending)

December 1, 2010

Ambient Environment

Operating Temperature Range: 0°C to 35°C

Storage Temperature Range: -20°C to 60°C

Relative Humidity Range: 0 to 100% (non-condensing)

Power Requirements

Less than 300 watts peak power at startup, practical use < 200 Watts for gas or liquid analyses

24 VDC supplied from external power supply, 100-240VAC using 50/60Hz AC

Safety

General purpose, light industrial (lab instrument environment)

CE Mark and Nationally Recognized Testing Laboratory (NRTL) certified pending (TUV Rheinland)

Gas Supplies

50 PSIG, 99.995% H₂ or He at up to 250 ml/min, 50 PSIG zero air for FID operation

Sample Requirements (via split/splitless injector with septum purge)

Air or gaseous samples at 0 to 50 PSIG at ambient temperature

Membrane, SPME and static and dynamic headspace extracts

Direct liquid injections neat or dilute organic solvents (DCM, hexane, MEK, toluene, methanol, CS₂ etc.)

Dimensions

17" wide by 8.5" deep by 11" high, ~ 20 lbs

Uninterrupted power supply and data acquisition computer external to the base unit

Controls/Outputs

All functions and parameters via ethernet or RS-232 using ChromPerfect™ software

Start analysis from keyboard or GC

Set method from external computer using ChromPerfect software

50-100Hz digitization (detector dependent) on each column, 24 bit resolution, auto zero on each run

Trigger in and ready out signals plus an array of others via ChromPerfect

Front Panel Displays

Temperature and pressure readings, function on/off, other

Power on/off

Status of analysis columns (isothermal, programming, cool down, ready, cycles run, other)

Standard Equipment

Two capillary columns, 2m long, 100µm to 320µm ID, temperature programmable from 0.1 to 5°C per second from 5° above ambient to 350°C (maximum temperature software limited to be no greater than the limit for the columns installed, isothermal operation is available). Column modules are 2 meter columns in Mxt-1, Mxt-5, Mxt-1701, Mxt-Wax, Mxt-MoleSieve, Mxt-Alumina, < 320µm and various film thicknesses with others coming soon.

Flame ionization or thermal conductivity (filament) detection

Gas and liquid inlet for syringe injection of samples or automated gas and liquid sample valves available

Performance (application dependent)

Repeatability of ± 1% RSD or better (area) and of ± 0.1% RSD or better (retention times)

Analysis times for VOCs: can be <20 seconds and for SVOCs: can be <60 seconds

Dynamic range: depends on detector used and application (FID typically 10⁵)


Data Processing and Instrument Control

Note: computer system is integral and necessary component of the analysis system and includes the following:

RS-232 or USB to RS-232 adapter, ethernet

Windows XP or newer operating environment

ChromPerfect software for dual column data acquisition via RS-232 serial or ethernet ports



Faster, Smaller, Smarter, Easier, Greener



UK Distribution by: IMA Ltd, Parkwell House, Otley Road, Guiseley, West Yorkshire, LS20 8BH, England

Tel: +44(0)1943 878877

Email: info@ima.co.uk

Website: www.ima.co.uk